

BATTERY MODEL#	GB TRAY#	DC VOLTS	AH CAPACITY		WEIGHT LBS	LEAD			ELECTROLYTE			SULFURIC (38% of ELECTROLYTE)		
			6 HR	20 HR		Min 43%	Max 70%	Avg 65%	Min 20%	Max 44%	Avg 25%	Min	Max	Avg
6-85-11	562	12	425	670	471	203	330	306	94	207	118	36	79	45
6-75-13	217	12	450	709	528	227	370	343	106	232	132	40	88	50
6-75-13	104	12	450	709	530	228	371	345	106	233	133	40	89	50
6-85-13	217	12	510	804	547	235	383	356	109	241	137	42	91	52
6-85-13	104	12	510	804	547	235	383	356	109	241	137	42	91	52
6-100-13	174	12	600	946	612	263	428	398	122	269	153	47	102	58
6-125-13	307	12	750	1182	735	316	515	478	147	323	184	56	123	70
12-85-5	163	24	170	268	500	215	350	325	100	220	125	38	84	48
12-85-5	152	24	170	268	500	215	350	325	100	220	125	38	84	48
12-85-7	377	24	255	402	616	265	431	400	123	271	154	47	103	59
12-85-7	179	24	255	402	616	265	431	400	123	271	154	47	103	59
12-75-13	201	24	450	709	1,055	454	739	686	211	464	264	80	176	100
12-75-13	133	24	450	709	1,050	452	735	683	210	462	263	80	176	100
12-85-13	201	24	510	804	1,094	470	766	711	219	481	274	83	183	104
12-85-13	133	24	510	804	1,094	470	766	711	219	481	274	83	183	104
12-85-15	265	24	595	938	1,245	535	872	809	249	548	311	95	208	118
12-85-15	357	24	595	938	1,240	533	868	806	248	546	310	94	207	118
12-85-19	175	24	765	1206	1,513	651	1,059	983	303	666	378	115	253	144
12-85-21	195	24	850	1340	1,652	710	1,156	1,074	330	727	413	126	276	157
12-85-23	393	24	935	1474	1,769	761	1,238	1,150	354	778	442	134	296	168
12-100-13	254	24	600	946	1,224	526	857	796	245	539	306	93	205	116
12-125-11	137	24	625	985	1,234	531	864	802	247	543	309	94	206	117
12-125-11	153	24	625	985	1,229	528	860	799	246	541	307	93	205	117
12-125-11	102	24	625	985	1,248	537	874	811	250	549	312	95	209	119
12-125-13	101	24	750	1182	1,470	632	1,029	956	294	647	368	112	246	140
12-125-13	488	24	750	1182	1,461	628	1,023	950	292	643	365	111	244	139
12-125-13	165	24	750	1182	1,468	631	1,028	954	294	646	367	112	245	139
12-125-13	103	24	750	1182	1,482	637	1,037	963	296	652	371	113	248	141
12-125-13	288	24	750	1182	1,473	633	1,031	957	295	648	368	112	246	140
12-125-15	155	24	875	1379	1,690	727	1,183	1,099	338	744	423	128	283	161
12-125-15	181	24	875	1379	1,710	735	1,197	1,112	342	752	428	130	286	162
12-125-15	252	24	875	1379	1,688	726	1,182	1,097	338	743	422	128	282	160
12-125-15	241	24	875	1379	1,695	729	1,187	1,102	339	746	424	129	283	161
12-125-17	183	24	1000	1576	1,858	799	1,301	1,208	372	818	465	141	311	177
18-85-13	385	36	510	804	1,641	706	1,149	1,067	328	722	410	125	274	156
18-85-13	187	36	510	804	1,652	710	1,156	1,074	330	727	413	126	276	157
18-85-15	318	36	595	938	1,868	803	1,308	1,214	374	822	467	142	312	177
18-85-15	331	36	595	938	1,879	808	1,315	1,221	376	827	470	143	314	179
18-85-17	278	36	680	1072	2,077	893	1,454	1,350	415	914	519	158	347	197
18-85-17	389	36	680	1072	2,092	900	1,464	1,360	418	920	523	159	350	199
18-85-17	110	36	680	1072	2,081	895	1,457	1,353	416	916	520	158	348	198
18-85-17	342	36	680	1072	2,099	903	1,469	1,364	420	924	525	160	351	199
18-85-17	229	36	680	1072	2,085	897	1,460	1,355	417	917	521	158	349	198
18-85-17	470	36	680	1072	2,103	904	1,472	1,367	421	925	526	160	352	200

BATTERY MODEL#	GB TRAY#	DC VOLTS	AH CAPACITY		WEIGHT LBS	LEAD			ELECTROLYTE			SULFURIC (38% of ELECTROLYTE)		
			6 HR	20 HR		Min 43%	Max 70%	Avg 65%	Min 20%	Max 44%	Avg 25%	Min	Max	Avg
18-85-19	683	36	765	1206	2,269	976	1,588	1,475	454	998	567	172	379	216
18-85-19	343	36	765	1206	2,273	977	1,591	1,477	455	1,000	568	173	380	216
18-85-19	176	36	765	1206	2,275	978	1,593	1,479	455	1,001	569	173	380	216
18-85-21	303	36	850	1340	2,479	1,066	1,735	1,611	496	1,091	620	188	414	236
18-85-23	134	36	935	1474	2,653	1,141	1,857	1,724	531	1,167	663	202	444	252
18-85-23	426	36	935	1474	2,681	1,153	1,877	1,743	536	1,180	670	204	448	255
18-85-25	177	36	1020	1608	2,898	1,246	2,029	1,884	580	1,275	725	220	485	275
18-85-25	367	36	1020	1608	2,930	1,260	2,051	1,905	586	1,289	733	223	490	278
18-85-27	349	36	1105	1742	3,142	1,351	2,199	2,042	628	1,382	786	239	525	298
18-85-29	346	36	1190	1876	3,350	1,441	2,345	2,178	670	1,474	838	255	560	318
18-85-31	811	36	1275	2010	3,619	1,556	2,533	2,352	724	1,592	905	275	605	344
18-85-33	136	36	1360	2144	3,930	1,690	2,751	2,555	786	1,729	983	299	657	373
18-100-17	427	36	800	1261	2,340	1,006	1,638	1,521	468	1,030	585	178	391	222
18-100-21	292	36	1000	1576	2,790	1,200	1,953	1,814	558	1,228	698	212	466	265
18-125-11	216	36	625	985	1,852	796	1,296	1,204	370	815	463	141	310	176
18-125-13	138	36	750	1182	2,205	948	1,544	1,433	441	970	551	168	369	209
18-125-15	158	36	875	1379	2,488	1,070	1,742	1,617	498	1,095	622	189	416	236
18-125-17	215	36	1000	1576	2,787	1,198	1,951	1,812	557	1,226	697	212	466	265
24-85-13	132	48	510	804	2,188	941	1,532	1,422	438	963	547	166	366	208
24-85-13	147	48	510	804	2,194	943	1,536	1,426	439	965	549	167	367	208
24-85-15	180	48	595	938	2,494	1,072	1,746	1,621	499	1,097	624	190	417	237
24-85-15	888	48	595	938	2,492	1,072	1,744	1,620	498	1,096	623	189	417	237
24-85-17	300	48	680	1072	2,770	1,191	1,939	1,801	554	1,219	693	211	463	263
24-85-17	354	48	680	1072	2,794	1,201	1,956	1,816	559	1,229	699	212	467	265
24-85-19	410	48	765	1206	3,026	1,301	2,118	1,967	605	1,331	757	230	506	287
24-85-21	299	48	850	1340	3,305	1,421	2,314	2,148	661	1,454	826	251	553	314
24-85-25	390	48	1020	1608	3,864	1,662	2,705	2,512	773	1,700	966	294	646	367
24-125-13	428	48	750	1182	2,940	1,264	2,058	1,911	588	1,294	735	223	492	279
24-125-13	493	48	750	1182	3,188	1,371	2,232	2,072	638	1,403	797	242	533	303
FS-16NP	<SAME	6	230	340	114	49	80	74	23	50	29	9	19	11
FS23S-6C413	<SAME	12	300	443	324	139	227	211	65	143	81	25	54	31
FS23S-24C617	<SAME	48	520	768	2,136	918	1,495	1,388	427	940	534	162	357	203